

# 2002 ATK 250/260 Enduro



## Standard Features

- Reliable Rotax Counterbalanced liquid-cooled engine
- 500cc-sized radiators
- Stainless Steel Brake Rotors
- 6-Speed Transmission
- Talon Billet Aluminum Hubs
- Answer Protaper Handlebars
- D.I.D. V6 O-ring drive chain
- Braided stainless steel brake lines
- Nickel Plated exhaust pipe
- Motion Pro and Barnett control cables
- Radialite rear sprocket with muc grooves

## Engine Type:

Liquid-Cooled, 2-stroke, single

## Displacement:

249cc/251cc

## Bore & Stroke

67.5/67.95 x 69.8mm

## Compression Ratio:

7.04:1

## Carburetion:

38mm Mikuni TMX

## Ignition

Electronic, 100w lighting output

## Starting System:

Kick

## Transmission:

6-Speed, Wide Ratio

## Fuel Capacity:

3.1 Gallon

## Wheel Base:

58.5"

## Rake/Trail:

26 degrees/4.2"

## Seat Height:

37.2"

## Ground Clearance:

13.5"

## Front Wheel Travel:

11.8"

## Rear Wheel Travel:

13.6"

## Front Brake:

Brembo Dual piston, 260mm stainless steel rotor

## Rear Brake:

Brembo Dual piston, 220mm stainless steel rotor

## Front Tire:

80/100-21

## Rear Tire:

100/100-21

## Final Drive:

D.I.D. V6 O-ring drive chain

## Dry Weight:

235 lbs

  
*Quality American Motorcycles*

1163 West 850 North

Centerville, UT 84014

Ph:(801)298-8288 Fax:(801)299-0710

Web: [www.atkusa.com](http://www.atkusa.com)

Specifications Subject to Change Without Notice