

2002 ATK 500/600 Dirt Tracker



Standard Features

- Talon quick change aluminum hubs
- Wheel base adjustable steering tube
- WP Roma front forks featuring rebound and compression control
- Tank-mounted heat shield for frame backbone
- Quick change chain slider
- Integrated clutch and decompression lever
- Rotax 865 cam
- Billet aluminum triple clamps
- AFAM Dirt Track aluminum handlebars
- Super Trapp stainless steel exhaust
- Motion Pro control cables

Engine Type:

Air-Cooled, 4-stroke, four valve, single

Displacement:

494cc/598cc

Bore & Stroke

89.0 x 79.4mm

97 x 81.0mm

Compression Ratio:

9.2:1/9.5:1

Carburetion:

38mm/40mm Dell'Orto

Ignition

Electronic, 190w lighting output

Starting System:

Electronic w/ Kick

Transmission:

5-Speed, Wide Ratio

Fuel Capacity:

3.6 Gallon

Wheel Base:

56.0"

Rake/Trail:

25 degrees/3.83"

Seat Height:

35.0"

Ground Clearance:

10.75"

Front Wheel Travel:

6.0"

Rear Wheel Travel:

8.5"

Front Brake:

Brembo 4 piston, 280mm floating stainless steel rotor

Rear Brake:

Brembo single piston, 220mm stainless steel rotor

Front Tire:

130/80-19

Rear Tire:

140/80-19

Final Drive:

D.I.D. V6 O-ring drive chain

Dry Weight:

272 lbs

US ATK

Quality American Motorcycles

1163 West 850 North

Centerville, UT 84014

Ph:(801)298-8288 Fax:(801)299-0710

Web: www.atkusa.com

Specifications Subject to Change Without Notice