



# 250/260 2-STROKE LIQUID GOOLED

Bulletproof liquid cooled twostroke Rotax engine combined with WP® suspension provides smooth power and incredible handling.

## 350/605 4-STROKE GROSS COUNTRY

Radical monoframe design offers low seat height and exceptional handling. A high-torque air/oil cooled four-stroke Rotax engine delivers power to spare.



# 350/605 4-STROKE DUAL SPORT

Hold on for the ride of your life—down the street or off the beaten path. The 4-stroke Rotax engine is a proven winner no matter where you go.

# 1997 FEATURES AND SPECIFICATIONS



Rotax four-stroke engine: massive torque and simple maintenance.



Brembo<sup>®</sup> brakes provide smooth reliable stopping power.



WP® competition level inverted 40mm cartridge forks. Billet aluminum triple clamps.



Answer® Protaper bars are strong and absorb shock.



WP® performance: race-tuned and fade free.



Rotax two-stroke engines feature sixspeed transmissions.



Competition-tuned exhaust in nickel or stainless finishes.



Oversized radiators keep engine cool for extended life.



Talon® machined billet aluminum hubs and stainless steel spokes.

### 250/260 LIQUID COOLED

ENGINE TYPE BORE AND STROKE CARBURETION IGNITION

250cc/251cc 2-stroke Rotax 67.5 x 69.8mm/67.65 x 69.8mm 35mm Mikuni TMX Electronic, 160 Watt lighting output

TRANSMISSION STARTING

6-speed, wide ratio Kick 3.1 gallons

FUEL CAPACITY WHEELBASE RAKE/TRAIL

58.5 inches 27 degrees, 4.7 inches

SEAT HEIGHT GROUND CLEARANCE FRONT WHEEL TRAVEL REAR WHEEL TRAVEL WEIGHT (WET, NO FUEL)

13.5 inches 11.8 inches 13.5 inches

37.2 inches

250 OPTIONS: 260 STD. EQUIPMENT: 230/235 pounds Lighting kit, skid plate, spark arrestor. Lighting kit, skid plate, spark arrestor.

### 350/605 CROSS COUNTRY

ENGINE TYPE BORE AND STROKE CARBURETION IGNITION 348cc/598cc air-cooled SOHC 4-stroke Rotax 79.5 x 70.4mm/97.0 x 81.0mm

34mm/40mm Dell 'Orto

TRANSMISSION

Electronic, 190 Watt lighting output 6/5-speed, wide ratio

STARTING FUEL CAPACITY Kick (electric optional)
3.6 gallons

WHEELBASE RAKE/TRAIL

59.0 inches 27 degrees, 4.7 inches

SEAT HEIGHT GROUND CLEARANCE FRONT WHEEL TRAVEL 36.5 inches

FRONT WHEEL TRAVEL
REAR WHEEL TRAVEL
WEIGHT (WET, NO FUEL)

11.8 inches 13.5 inches 258/260 pounds

OPTIONS:

Lighting kit

### **350/605 DUAL SPORT**

ENGINE TYPE BORE AND STROKE

348cc/598cc air-cooled SOHC 4-stroke Rotax

CARBURETION

79.5 x 70.4mm/97.0 x 81.0mm 34mm/40mm Dell 'Orto

CARBURETION IGNITION

Electronic, 190 Watt lighting output

TRANSMISSION

6/5-speed, wide ratio Kick and electric

STARTING FUEL CAPACITY

3.6 gallons 59.0 inches

WHEELBASE RAKE/TRAIL

27 degrees, 4.7 inches

SEAT HEIGHT GROUND CLEARANCE 36.5 inches 13.0 inches

FRONT WHEEL TRAVEL
REAR WHEEL TRAVEL

11.8 inches 13.5 inches

WEIGHT (WET, NO FUEL)

278/280 pounds



1164 West 850 North, Centerville, Utah 84014 Telephone: (801) 298-8288 Fax: (801) 299-0710 Internet: www.atkusa.com