

250/260 2-STROKE OFF-ROAD

New frame geometry and improved low-end engine response provide exceptional off-road performance.

350/605 4-STROKE CROSS COUNTRY/ENDURO

Radical monoframe design offers low seat height and exceptional handling. A high-torque air/oil cooled four-stroke Rotax engine delivers power to spare.



600 4-STROKE DIRT TRACK

With a potent 600 cc Rotax engine, wrapped in a revolutionary frame, this factory-built dirt tracker is a race-proven winner.

1998 FEATURES AND SPECIFICATIONS



Rotax four-stroke engine: massive torque and simple maintenance.



Brembo[®] brakes provide smooth reliable stopping power.



WP® competition level inverted 40mm cartridge forks. Billet aluminum triple clamps.



Answer® Protaper bars are strong and absorb shock.



WP® performance: race-tuned and fade free.



Rotax two-stroke engines feature sixspeed transmissions.



Competition-tuned exhaust in nickel or stainless finishes.



Oversized radiators keep engine cool for extended life.



Talon® machined billet aluminum hubs and stainless steel spokes.

250/260 2-STROKE

ENGINE TYPE 249cc/251cc 2-stroke Rotax
BORE AND STROKE 67.5 x 69.8mm/67.75 x 69.8mm
CARBURETION 35mm Mikuni TMX

IGNITION Electronic, 160 Watt lighting output

TRANSMISSION 6-speed, wide ratio

STARTING Kick
FUEL CAPACITY 3.1 gallons
WHEELBASE 58.5 inches

RAKE/TRAIL 26 degrees, 4.2 inches

SEAT HEIGHT 37.2 inches
GROUND CLEARANCE 13.5 inches
FRONT WHEEL TRAVEL 11.8 inches
REAR WHEEL TRAVEL 13.6 inches
WEIGHT (WET, NO FUEL) 230/235 pounds

250 OPTIONS: Lighting kit, skid plate, spark arrestor.
260 STD. EQUIPMENT: Lighting kit, skid plate, spark arrestor.

350/605 4-STROKE

ENGINE TYPE

348cc/598cc air-cooled SOHC 4-stroke Rotax
BORE AND STROKE

79.5 x 70.4mm/97.0 x 81.0mm

CARBURETION

34mm/40 mm Dell 'Orto

Electronic, 190 Watt lighting output

TRANSMISSION 6/5-speed, wide ratio
STARTING Kick (electric optional)
FUEL CAPACITY 3.6 gallons

FUEL CAPACITY 3.6 gallons
WHEELBASE 59.0 inches

RAKE/TRAIL 27 degrees, 4.7 inches SEAT HEIGHT 36.5 inches

GROUND CLEARANCE 13.0 inches
FRONT WHEEL TRAVEL 11.8 inches
REAR WHEEL TRAVEL 13.2 inches
WEIGHT (WET, NO FUEL) 258/260 pounds
OPTIONS: Lighting kit

600 DIRT TRACK

ENGINE TYPE 598cc air-cooled SOHC 4-stroke Rotax

BORE AND STROKE 97.0 x 81.0mm
CARBURETION 40 mm Dell 'Orto

IGNITION Electronic, 190 Watt lighting output

TRANSMISSION 5-speed, wide ratio
STARTING Bump/electric
FUEL CAPACITY 3.6 gallons
WHEELBASE 56 inches

RAKE/TRAIL 25 degrees, 3.83 inches

SEAT HEIGHT 33 inches
GROUND CLEARANCE 10.75 inches
FRONT WHEEL TRAVEL 6 inches
REAR WHEEL TRAVEL 8.5 inches
WEIGHT (WET, NO FUEL) 255 pounds



1164 West 850 North, Centerville, Utah 84014 Telephone: (801) 298-8288 Fax: (801) 299-0710 Internet: www.atkusa.com