

2002 ATK 125 Enduro



Standard Features

- Reliable Rotax Counterbalanced liquid-cooled engine
- 500cc-sized radiators
- Stainless Steel Brake Rotors
- 6-Speed Transmission
- Talon Billet Aluminum Hubs
- Answer Protaper Handlebars
- D.I.D. V6 O-ring drive chain
- Braided stainless steel brake lines
- Nickel Plated exhaust pipe
- Motion Pro and Barnett control cables
- Radialite rear sprocket with muc grooves

Engine Type:

Liquid-Cooled, 2-stroke, single

Displacement:

124.9cc

Bore & Stroke

54mm x 54.4mm

Carburetion:

35mm Mikuni TMX

Ignition

Electronic, 100w lighting output

Starting System:

Kick

Transmission:

6-Speed, Wide Ratio

Fuel Capacity:

3.1 Gallon

Wheel Base:

57.5"

Rake/Trail:

26 degrees/4.1"

Seat Height:

37.5"

Ground Clearance:

13.5"

Front Wheel Travel:

11.8"

Rear Wheel Travel:

13.6"

Front Brake:

Brembo single piston, 260mm stainless steel rotor

Rear Brake:

Brembo single piston, 220mm stainless steel rotor

Front Tire:

80/100-21

Rear Tire:

100/100-21

Final Drive:

D.I.D. V6 520 O-ring drive chain

Dry Weight:

227 lbs

US ATK
Quality American Motorcycles

1163 West 850 North
Centerville, UT 84014

Ph:(801)298-8288 Fax:(801)299-0710

Web: www.atkusa.com