2002 ATK 500 Enduro



Standard Features

- Reliable Rotax Air-Cooled Engine with Electronic and Kick starting
- Paioli Conventional 46mm Forks
- Ohlins POS Shock
- 6-Speed Transmission
- Talon Billet Aluminum Hubs
- Answer Protaper Handlebars
- D.I.D. V6 O-ring drive chain
- Braided stainless steel brake lines
- Nickel Plated exhaust pipe
- Motion Pro and Barnett control cables
- Radialite rear sprocket with muc grooves
- Halogen Headlight
- DOT approved Dunlop tires
- Keyed Ignition



Quality American Motorcycles 1163 West 850 North Centerville, UT 84014 Ph:(801)298-8288 Fax:(801)299-0710 Web: www.atkusa.com **Engine Type:**

Displacement: Bore & Stroke Compression Ratio: Carburetion: Ignition

Starting System: Transmission: Fuel Capacity: Wheel Base: Rake/Trail: Seat Height: Ground Clearance: Front Wheel Travel: Rear Wheel Travel: Front Brake:

Rear Brake:

Front Tire: Rear Tire: Final Drive:

Dry Weight:

Air-Cooled, 4-stroke, four valve, single 494cc 89 x 79.4mm 9.2:1 38mm Dell'Orto Electronic, 190w lighting output Electronic w/ Kick 5-Speed, Wide Ratio 3.6 Gallon 59.0" 27 degrees/4.7" 36.5" 13.0" 11.8" 13.2" Brembo Dual piston, 260mm stainless steel rotor Brembo Dual piston, 220mm stainless steel rotor 80/100-21 110/100-18 D.I.D. V6 O-ring drive chain 289 lbs

Specifications Subject to Change Without Notice