

2003 ATK 250/260 Enduro



Standard Features

- Reliable Rotax Counterbalanced liquid-cooled engine
- 500cc-sized radiators
- Stainless Steel Brake Rotors
- 6-Speed Transmission
- Talon Billet Aluminum Hubs
- Answer Protaper Handlebars
- D.I.D. V6 O-ring drive chain
- Braided stainless steel brake lines
- Nickel Plated exhaust pipe
- Motion Pro and Barnett control cables
- Radialite rear sprocket with muc grooves

Engine Type:

Displacement:

Bore & Stroke

Compression Ratio:

Carburetion:

Ignition

Starting System:

Transmission:

Fuel Capacity:

Wheel Base:

Rake/Trail:

Seat Height:

Ground Clearance:

Front Wheel Travel:

Rear Wheel Travel:

Front Brake:

Rear Brake:

Front Tire:

Rear Tire:

Final Drive:

Dry Weight:

Liquid-Cooled, 2-stroke, single

249cc/251cc

67.5/67.95 x 69.8mm

7.04:1

38mm Mikuni TMX

Electronic, 100w lighting output

Kick

6-Speed, Wide Ratio

3.1 Gallon

58.5"

26 degrees/4.2"

37.2"

13.5"

11.8"

13.6"

Brembo Dual piston, 260mm stainless steel rotor

Brembo Dual piston, 220mm stainless steel rotor

80/100-21

100/100-21

D.I.D. V6 O-ring drive chain

235 lbs

US ATK
Quality American Motorcycles

1163 West 850 North

Centerville, UT 84014

Ph:(801)298-8288 Fax:(801)299-0710

Web: www.atkusa.com

Specifications Subject to Change Without Notice