2008 450 MOTARD

Preliminary Specifications



Standard Features

- High Performance Lightweight 4-Stroke •
- Fuel Injected •
- Electric Start ٠
- Ohlins POS Fully Adjustable Shock •
- Ohlins 46mm Fully Adjustable Fork
- Aluminum Twin-Spar Frame •
- Perimeter Frame •
- Aluminum Removable Subframe •
- Gold Billet Hubs w Black Excel Wheels
- Wire Harness for Lights

Options

- Automatic Clutch
- Handguards
- On the Fly Map Select
- 320mm Front Brake Rotor
- **Oversize Piston Front Brake Caliper** •

New for 2008

- **New Falicon Stroker Crankshaft**
- **New Aluminum Nikasil Cylinder**
- New Bore and Stroke for Max Power
- **New Fuel Injection Settings**
- New Kickstand
- **New Graphics**
- **New Improved Seat**
- **Additional Options**



1163 West 850 North Centerville, UT 84014 (801) 298-8288 Fax:(801) 299-0710 Web: www.atkusa.com

Engine Type:

Displacement: Bore & Stroke Horsepower / RPM **Compression Ratio:** Carburetion: Ignition

Starting System: Transmission: Clutch: **Fuel Capacity:** Wheel Base: Frame: Seat Height: **Ground Clearance:** Front Suspension: **Rear Suspension:**

Liquid, 4-Stroke Single DOHC 4- Valve Head 449cc 95.0 x 63.4 48HP @ 10,000 RPM 12.3:1 **Fuel Injection** 12v Battery w Constant Energy Inductive Coil **Electronic Start** 5-Speed Cassette Hvdraulic 2.0 Gallon 58.5." Aluminum Twin-Spar 36.0" 12.2" 46mm Ohlins 10" Travel Ohlins POS 10" Travel 2 Piston, 240mm Rotor 2 piston, 220mm Rotor

MSRP \$8,495

Specifications Subject to Change without Notice 7.1.07

120/70-17

150/80-17

242 lbs

NO Warranty Included

Front Brake: **Rear Brake:** Front Tire: Rear Tire: Dry Weight: